

# E30A



## Highlights

- \_ Stage-II vapour recovery system
- \_ Flowrate selector (40 - 80L/min)
- \_ High flow (80L/min) and very high flow (120L/min) configurations
- \_ Designed following the "Design for Everyone" criteria for persons with reduced mobility
- \_ Electromechanical totalizers
- \_ Satellite column with remote customer display
- \_ Payment terminal
- \_ Ready for third party payment terminals
- \_ Ready for third party multimedia systems
- \_ AdBlue

# E30A

## EAS2 Electronic Calculator

Designed for the future. Modular and scalable: the cost is adapted to the customer's needs.

Designed to minimize the downtime.

Attractive and simple user interface.

Different access levels to increase security.

International IFSF-LON protocol available.

EC Type Examination Certificate (MID) issued by NMI  
No. T10544 & T10545

OIML Certificate of Conformity issued by NMI  
No. R117/1995-NL1-15.01

EC Type Examination Certificate (ATEX) issued by LOM  
No. LOM I3ATEX2057

## Main features of the E30 series dispensers

### Standard

- Electronic calibration
- Optical product identification
- Preset
- Chassis and cladding manufactured with galvanized F114 steel
- Anticorrosive epoxy primer; oven-cured polyester powder paint
- Antigraffiti coating

### Options

- Stainless steel
- Acoustic product identification (several languages available)
- Intercom system
- Flowrate selector
- Ambient temperature indicator
- Electromechanical totalizers

The maximum flow rates indicated may be influenced by the installation, altitude of the service station and ambient temperature



Cetil Dispensing Technology, S.L.  
Pelaya, 37 (P.I. Río de Janeiro)  
28110 Algete (Madrid) Spain  
Phone: (+34) 916 287 651  
Fax: (+34) 916 287 653  
[cefil@cefil.com](mailto:cefil@cefil.com) | [www.cefil.com](http://www.cefil.com)

